

Series EKT8



Thermostat for Refrigeration EKT853


FTPT03-0221_121001



FEATURES:

- Internal buzzer and real time clock (Optional).
- 16A Compressor relay (2HP relay optional).
- Relay 2, relay 3, relay 4 and relay 5 configurable for light, fan, alarm or defrost control. Relay 4 also can be configured for second compressor control.
- Intelligent defrost and night set to reduce the power consumption.
- HACCP Logging.
- Power connections with screw terminal block or faston terminals.
- Models with direct load connections.
- 90-255Vac 50/60Hz supply voltage.
- RS485 Communication by external module KLRS485A.
- Models with communication module permit total control and monitoring from a PC.
- Easy access to parameters by code.
- °C / °F selectable by parameter.

HOW TO ORDER:



AVAILABLE MODELS:

- EKT853HBRDTLR90255
- EKT853HBRDFLR90255

SPECIFICATIONS:

Panel mounting

Cutout: 150 x 31 mm (5.90 x 1.22 inch)

Dimensions

Front: 184 x 39 mm (7.24 x 1.53 inch)

Depth: 64 mm (2.52 inch)

Measurement range

-50°C to 150°C / -58°F to 302°F

Accuracy

Better than 1% of full scale

Resolution

0.1°

Probes

3 PTC (1000 Ohms, 25°C) / NTC probes

Outputs

OUT1: SPST Relay Resistive load 20A

2HP 240Vac -- 12FLA, 72LRA 240Vac

OUT2: SPDT Relay Resistive load 8A

OUT3: SPST Relay Resistive load 8A



OUT4, OUT5: SPDT Relay Resistive load 16A

HP 240Vac -- 10FLA, 60LRA 240Vac

IP Protection

Front: IP65 / Back: IP20

WIRING CONNECTIONS:



HEADQUARTERS

Polígono Empresarial. C/Lentisco, 15.
50720 La Cartuja Baja. Zaragoza. (Spain).
Tel: +34 976 429 099 · Fax: +34 976 593 532.
E-mail: keld@keld.es · web: www.keld.es
GPS: N 41.5863 W 0.82531

Keld México

Av. Chapultepec No. 148.
Col. Roma C.P. 06700.
Del Cuauhtemoc, México D.F.

Keld China. Jiaxing factory:

D-1 #4 Building. No289 Muyang RD.
Jiaxing Economic Develop Zone.
Jiaxing. China.