

Series KLH01



Humidity Indicator KLH01

FTPT01-006I_121001



FEATURES:

- Hygrometer with one input probe and powered directly from the mains.
- High visibility (led display).
- 3 digits (without tenths).
- Probe type 0-3V.
- Error probe indication.
- Connection by screw terminal blocks.

SPECIFICATIONS:

Panel Mounting

Cutout: 71 x 29 mm (2.79 x 1.14 inch)

Dimensions

Front: 76,5 x 36 mm (3.01 x 1.41 inch)

Depth: 60 mm (2.36 inch)

Measurement range

0 to 100 % RH

Accuracy

+/- 1% RH

Resolution

+/- 1% RH from -9.9^o to 9.9^o (1^o out of this range)

Probe

0 - 3V


IP Protection

Front: IP64

Rear: IP20

HOW TO ORDER:

MODELS: KLH01-G230



Options: Ask to factory


AVAILABLE MODELS:

- KLH01-G230
- KLH01-G110

WIRING CONNECTIONS:

Input probe

In GND Vcc



%Hr



Power supply



HEADQUARTERS

Polígono Empresarial. C/Lentisco, 15.
50720 La Cartuja Baja. Zaragoza. (Spain).
Tel: +34 976 429 099 · Fax: +34 976 593 532.
E-mail: keld@keld.es · web: www.keld.es
GPS: N 41.5863 W 0.82531



Keld México

Av. Chapultepec No. 148.
Col. Roma C.P. 06700.
Del Cuauhtemoc, México D.F.

Keld China. Jiaxing factory:
D-1 #4 Building. No289 Muyang RD.
Jiaxing Economic Develop Zone.
Jiaxing. China.